


DORADO PL

PLAFONE / CEILING

Parete / plafone / terra Wall / ceiling / floor



01 Bianco White 02 Nero Black 07 Oro Gold



-L10 1 m 0.48 Kg
-L20 2 m 0.96 Kg

| Codice base Base code | Ottica Optic | Fissaggio Fixing | Colour T (K) | Finitura Finish | Chiusura Closing |
|--------------------------|-----------------|---------------------|-----------------|--------------------|---------------------|
|--------------------------|-----------------|---------------------|-----------------|--------------------|---------------------|

Profilo orientabile. Customizzabile fino a 4m
Adjustable profile. Customizable up to 4m

| | | | | | |
|-------|----------------|----|---------|----|-----|
| DR2 - | O opale / opal | PL | Z 2700K | 01 | L10 |
| | | | C 3000K | 02 | L20 |
| | | | N 4000K | 07 | |

24Vdc

CE IP20

Caratteristiche illuminotecniche / Lighting specifications

| Dimensione Size (mm) | LED Lumen | Product Lumen | | Watt | Vdc | Colour T | CRI |
|-------------------------|--------------|------------------|-----------|------|-----|-------------|-----|
| | | opal | prismatic | | | | |
| 1004 | 1900 | 1330 | - | 16 | 24 | 2700 | 93 |
| | 2000 | 1400 | - | 16 | 24 | 3000 | 93 |
| | 2100 | 1470 | - | 16 | 24 | 4000 | 93 |
| 2004 | 3800 | 2660 | - | 32 | 24 | 2700 | 93 |
| | 4000 | 2800 | - | 32 | 24 | 3000 | 93 |
| | 4200 | 2940 | - | 32 | 24 | 4000 | 93 |

Driver da ordinare separatamente / Drivers to be ordered separately

07250 Output 24Vdc 75W
On/Off

Controller da ordinare separatamente
Controller to be ordered separately

CT00050 Dimmer 1 ch
DALI2-PUSH-0/1..10V

CT00052 Dimmer 1 ch
PUSH/WIRELESS

Reference configurator

Il codice prodotto si compone mettendo in fila, da sinistra a destra, i dati contenuti nelle colonne a partire da "Codice base".

The product code is created by putting in sequence the data starting from "Base code", from left to right.

es: DR2-2PLZ01L10

