


# HYDRA OUTDOOR



00 Alluminio  
Aluminium



**-L06**  
0,606 m  
0,70 Kg

**-L12**  
1,206 m  
1,40 Kg

**-L18**  
1,806 m  
2,10 Kg

Codice base Base code	Ottica Optic	Fissaggio Fixing	Colour T (K)	Finitura Finish	Chiusura Closing
--------------------------	-----------------	---------------------	-----------------	--------------------	---------------------

Variante da comporre a seconda delle proprie necessità  
Variant to compose according to your needs

<b>HY -</b>	<b>O</b> opale / opal	<b>PL</b>	<b>Z</b> 2700K	<b>00</b>	<b>L06</b>
			<b>C</b> 3000K		<b>L12</b>
			<b>N</b> 4000K		<b>L18</b>

24Vdc

CE IP65

## Caratteristiche illuminotecniche / Lighting specifications

Dimensione Size (mm)	LED Lumen	Product Lumen		Watt	Vdc	Colour T	CRI
		opal	prismatic				
606	1017	712	-	8,6	24	2700	93
	1070	749	-	8,6	24	3000	93
	1124	786	-	8,6	24	4000	93
1206	2170	1519	-	18,3	24	2700	93
	2284	1599	-	18,3	24	3000	93
	2398	1679	-	18,3	24	4000	93
1806	3257	2280	-	27,4	24	2700	93
	3428	2400	-	27,4	24	3000	93
	3599	2520	-	27,4	24	4000	93

Driver da ordinare separatamente / Drivers to be ordered separately

**07250** Output 24Vdc 75W  
On/Off

Controller da ordinare separatamente  
Controller to be ordered separately

**CT00050** Dimmer 1 ch  
DALI2-PUSH-0/1..10V

**CT00052** Dimmer 1 ch  
PUSH/WIRELESS

## Reference configurator

Il codice prodotto si compone mettendo in fila, da sinistra a destra, i dati contenuti nelle colonne a partire da "Codice base".

The product code is created by putting in sequence the data starting from "Base code", from left to right.

es: HY-OPLZ07L12

